

PXM PLATFORM CEF SPECIFICATION

VERSION 6.1.1



This document details a list of events that the PXM Platform can emit in Common Event Format (CEF) over the syslog protocol (see RFC3164). CEF is a standard in security event management that aids the interoperability of infrastructure devices by aggregating the logging output of different network devices and applications. As such, processing and analysing logged data can be streamlined, providing efficient access to semantically structured event data using a SIEM (Security Information and Event Management) approach.

ad_missing_account

A control account was missing from Active Directory

destinationUserName

Always

The account on the target device to which the event relates

account_updated

An account configuration has been updated on the PXM Platform

destinationUserName

Always

The account on the target device to which the event relates

deviceAction

Always

The update action performed on the account

destinationHostName

When Available

The host name of the device relating to the event

sourceUserName

When Available

The username of the platform user who initiated the action

authenticationServiceName (*as deviceCustomString4*)

When Available

The name of the authentication service associated with the account

destinationName (*as deviceCustomString1*)

When Available

The name of the device relating to the event

newState (*as deviceCustomString5*)

When Available

The new state of the account

destinationAddress

When Available

The address of the device relating to the event

sourceUserDisplayName (*as deviceCustomString2*)

When Available

The human-readable name of the platform user who initiated the action

oldState (*as deviceCustomString6*)

When Available

The previous state of the account

api_content_changed

The resource at an API path was updated

auth_service_connection_error

Failed to connect to an auth service

device_account_created

New account created on device

destinationHostName Always

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

device_account_deleted

Account deleted on device

destinationHostName Always

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

device_account_discovered

Discovered new unapproved account on device

destinationHostName Always

The host name of the device relating to the event

destinationName *(as deviceCustomString1)* Always

The name of the device relating to the event

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

device_account_missing

An account was no longer found on a device

destinationUserName Always

The account on the target device to which the event relates

device_granted_user_access

A user has been granted access to a device

destinationName *(as deviceCustomString1)* Always

The device to which the user was granted access

device_parameter_change_task_success

Successfully executed actions after parameter change

device_parameter_changed

Changed device parameter

toValue (*as deviceCustomString6*) Always

The new value of the parameter

destinationHostName Always

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

parameterName (*as deviceCustomString4*) Always

The name of the parameter that was changed

destinationAddress Always

The address of the device relating to the event

fromValue (*as deviceCustomString5*) When Available

The old value of the parameter

disk_capacity

Disk capacity checked.

error

An error has occurred

message Always

A message describing the error

sourceUserName When Available

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) When Available

The human-readable name of the platform user who initiated the action

external_filestore_mount

The external filestore mount status was checked

licence_status

The licence has been checked

long_running_connection_to_device

A user has been connected to a device for a long time

roleName (*as deviceCustomString5*) Always

The name of the role in which the user connected to the device

sourceUserName Always

The username of the platform user who initiated the action

changeTicketNames (*as deviceCustomString6*) Always

The names of any change tickets associated with the connection

channelToken (*as deviceCustomString4*) Always

An arbitrary identifier useful for correlating events pertaining to this connection

duration (*as deviceCustomNumber1*) Always

The length of time the user has been connected that is now considered to be "long"

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationAddress Always

The address of the device relating to the event

sourceAddress Always

The address from which the user connected to the device

applicationProtocol Always

The protocol used to communicate with the device

destinationUserName Always

The account on the target device to which the event relates

MAPToolName (*as deviceCustomString2*) When AvailableThe name of the MAP tool used

no_device_control_accountA device's Control Account has been marked as deleted

pbm_login_from_new_address

A user has logged in from an address they haven't used recently

destinationName (*as deviceCustomString1*) Always

The device to which the user logged in

destinationUserName Always

The username which logged in

password_viewed_on_console

A password was revealed on the break-glass console

destinationHostName Always

The host name of the device relating to the event

destinationName (as deviceCustomString1) Always

The name of the device relating to the event

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

radius_status

The radius server status was checked

sent_mail

Mail was sent, or failed to send

session_recording_status

There was an attempt to receive and store a session recording screenshot

session_terminated

An administrator terminated a session

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (as deviceCustomString2) Always

The human-readable name of the platform user who initiated the action

task_finished

An automated task was completed

destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
eventOutcome	Always
The success/failure status of the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationAddress	Always
The address of the device relating to the event	
taskName (<i>as deviceCustomString6</i>)	When Available
The name assigned to the task that completed	

task_queued

A task was queued to run

destinationHostName	Always
The host name of the device relating to the event	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
taskName (<i>as deviceCustomString6</i>)	Always
The name assigned to the queued task	
destinationAddress	Always
The address of the device relating to the event	
sourceUserName	When Available
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	When Available
The human-readable name of the platform user who initiated the action	

user_acquired_change_ticket

A user acquired a change ticket

changeTicketName (*as deviceCustomString6*) Always

The name of the change ticket acquired by the user

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

destinationUserName Always

The user who has been associated with the change ticket

user_associated_change_ticket_with_connection

A user associated a change ticket with a connection

changeTicketName (*as deviceCustomString6*) Always

The name of the change ticket associated with the connection

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

externalID Always

The arbitrary identifier of the connection associated with the change ticket

user_cloned_user

A user created new user by copying portions of an existing user

sourceUserName Always

The username of the platform user who initiated the action

destinationUserName Always

The username of the new user

clonedUserName (*as deviceCustomString2*) Always

The username of the user from which the new user was derived

emailAddress (*as deviceCustomString3*) When Available

The email address of the new user

expiresAt (*as deviceCustomString4*) When Available

When the new user account is set to expire

authenticationType (*as deviceCustomString6*) When Available

The authentication type of the new user

enabled (*as deviceCustomString5*) When Available

Whether the new user is enabled

user_commented_on_change_ticket

A user commented on a change ticket

sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
changeTicketName (<i>as deviceCustomString6</i>)	Always
The name of the change ticket on which the user commented	

user_connected_to_device

A user connected to a device using the PxM Platform

roleName (<i>as deviceCustomString5</i>)	Always
The name of the role in which the user connected to the device	
sourceUserName	Always
The username of the platform user who initiated the action	
changeTicketNames (<i>as deviceCustomString6</i>)	Always
The names of any change tickets associated with the connection	
channelToken (<i>as deviceCustomString4</i>)	Always
An arbitrary identifier useful for correlating events pertaining to this connection	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationAddress	Always
The address of the device relating to the event	
sourceAddress	Always
The address from which the user connected to the device	
applicationProtocol	Always
The protocol used to communicate with the device	
destinationUserName	Always
The account on the target device to which the event relates	
MAPToolName (<i>as deviceCustomString2</i>)	When Available
The name of the MAP tool used	

user_created_account_mapping_pattern

A user created a new account mapping pattern

pattern (<i>as deviceCustomString6</i>)	Always
The newly created account mapping pattern	
sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_created_auth_service

A user created an authentication service

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

authenticationServiceName (*as deviceCustomString6*) Always

The name of the authentication service

user_created_file

A user created a file stored on the PxM Platform

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

destinationHostName When Available

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) When Available

The name of the device relating to the event

destinationAddress When Available

The address of the device relating to the event

user_created_user

A user created a new user on the PxM Platform

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

destinationUserName Always

The username of the new user

authenticationType (*as deviceCustomString6*) When Available

The authentication type of the new user

enabled (*as deviceCustomString5*) When Available

Whether the new user is enabled

emailAddress (*as deviceCustomString3*) When Available

The email address of the new user

expiresAt (*as deviceCustomString4*) When Available

When the new user account is set to expire

user_created_user_group

A user created a new user group

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

userGroupName (*as deviceCustomString6*) Always

The name of the new user group

userNames (*as deviceCustomString5*) Always

The usernames of the users in the new user group

user_deleted_account_mapping_pattern

A user deleted an account mapping pattern

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

pattern (*as deviceCustomString6*) Always

The account mapping pattern that was deleted

user_deleted_auth_service

A user deleted an authentication service

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

authenticationServiceName (*as deviceCustomString6*) Always

The name of the authentication service

user_deleted_file

A user deleted a file stored on the PxM Platform

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

filePath Always

The full path of the file that was deleted, including the file name

destinationHostName When Available

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) When Available

The name of the device relating to the event

destinationAddress When Available

The address of the device relating to the event

user_deleted_user

A user deleted a user from the PxM Platform

destinationUserName Always

The username of the user that was deleted

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

user_deleted_user_group

A user deleted a user group

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

userGroupName (*as deviceCustomString6*) Always

The name of the deleted user group

user_disconnected_from_device

A user disconnected from a device

roleName (*as deviceCustomString5*) Always

The name of the role in which the user connected to the device

sourceUserName Always

The username of the platform user who initiated the action

changeTicketNames (*as deviceCustomString6*) Always

The names of any change tickets associated with the connection

channelToken (*as deviceCustomString4*) Always

An arbitrary identifier useful for correlating events pertaining to this connection

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationAddress Always

The address of the device relating to the event

sourceAddress Always

The address from which the user connected to the device

applicationProtocol Always

The protocol used to communicate with the device

destinationUserName Always

The account on the target device to which the event relates

MAPToolName (*as deviceCustomString2*) When Available

The name of the MAP tool used

user_downloaded_breakglass_document

A user downloaded the breakglass document

sourceUserName Always

The username of the platform user who initiated the action

user_executed_troubleshooting_script

A user executed a troubleshooting script on the PxM Virtual Application console

fileName Always

The name of the script that was executed on the console

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

sourceUserName Always

The username of the platform user who initiated the action

scriptArguments (*as deviceCustomString6*) Always

The arguments passed to the script

user_failed_login_odc

A user failed to log in using the PxM Client

destinationHostName	Always
The host name of the device relating to the event	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationUserName	Always
The account on the target device to which the event relates	
destinationAddress	Always
The address of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
sourceAddress	Always
The address from which the client attempted to connect	
message	When Available
An error message about why the login attempt failed	

user_failed_to_update_device_password

A user failed to update the password on a device

destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
destinationUserName	Always
The account on the target device to which the event relates	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationAddress	Always
The address of the device relating to the event	
reason	Always
The reason the password update did not proceed	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_forced_secrets_refresh

A user forced a password refresh for an account

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

destinationUserName Always

The account on the target device to which the event relates

authenticationServiceName (*as deviceCustomString6*) When Available

The authentication service to which the account belongs

destinationHostName When Available

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) When Available

The name of the device relating to the event

destinationAddress When Available

The address of the device relating to the event

user_locked_device_account

A user locked an account on a device

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

destinationUserName Always

The account on the target device to which the event relates

user_logged_in_odc

A user logged in using the PxM Client

destinationHostName Always

The host name of the device relating to the event

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

sourceAddress Always

The address from which the client connected

sourceUserName Always

The username of the platform user who initiated the action

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

user_logged_out_odc

A user logged out using the PxM Client

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationHostName Always

The host name of the device relating to the event

sourceUserName Always

The username of the platform user who initiated the action

sourceAddress Always

The address from which the client was connected

destinationUserName Always

The account on the target device to which the event relates

destinationAddress Always

The address of the device relating to the event

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

user_lowered_device_alert

A user lowered the alert for a device

destinationHostName Always

The host name of the device relating to the event

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (*as deviceCustomString2*) Always

The human-readable name of the platform user who initiated the action

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

destinationAddress Always

The address of the device relating to the event

user_migrated_device_to_new_template

A user migrated a device to use a new template

destinationHostName Always

The host name of the device relating to the event

sourceUserName Always

The username of the platform user who initiated the action

oldTemplateVersion (*as deviceCustomString3*) Always

The version of the device templated that was used to handle the device configuration and interactions

oldTemplateName (*as deviceCustomString2*) Always

The name of the device template that was used to handle the device configuration and interactions

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

newTemplateName (*as deviceCustomString4*) Always

The name of the device template that will now be used to handle the device configuration and interactions

destinationAddress Always

The address of the device relating to the event

templateVendor (*as deviceCustomString6*) Always

The vendor of the device that the template is targeting

newTemplateVersion (*as deviceCustomString5*) Always

The version of the device templated that will now be used to handle the device configuration and interactions

user_opened_device_connection

A user opened a device connection using the PxM Platform

sourceUserName Always

The username of the platform user who initiated the action

destinationName (*as deviceCustomString1*) Always

The name of the device relating to the event

user_provisioned_device

A user provisioned a device

destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationAddress	Always
The address of the device relating to the event	
templateVendor (<i>as deviceCustomString6</i>)	Always
The vendor of the device that the template is targeting	
templateName (<i>as deviceCustomString4</i>)	Always
The name of the device template used to handle the device configuration and interactions	
templateVersion (<i>as deviceCustomString5</i>)	Always
The version of the device templated used to handle the device configuration and interactions	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
authServiceName (<i>as deviceCustomString3</i>)	When Available
The human-readable name of the auth service the device was provisioned with	

user_read_device_file

A user read the contents of a file on a device

destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
filePath	Always
The full path on the device of the file that was read	
destinationUserName	Always
The account on the target device to which the event relates	
destinationAddress	Always
The address of the device relating to the event	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_released_change_ticket

A user released a change ticket

sourceUserName	Always
The username of the platform user who initiated the action	
changeTicketName (<i>as deviceCustomString6</i>)	Always
The name of the change ticket released by the user	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
destinationUserName	When Available
The username of the user who was associated with the change ticket	

user_requested_profile_deletion

A user requested the deletion of a profile

sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
sourceUserName	Always
The username of the platform user who initiated the action	
profileName (<i>as deviceCustomString6</i>)	Always
The name of the profile to be deleted	

user_revealed_secrets

A user revealed the secrets for an account

sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
destinationUserName	Always
The account on the target device to which the event relates	
authenticationServiceName (<i>as deviceCustomString6</i>)	When Available
The authentication service to which the account belongs	
destinationHostName	When Available
The host name of the device relating to the event	
destinationName (<i>as deviceCustomString1</i>)	When Available
The name of the device relating to the event	
destinationAddress	When Available
The address of the device relating to the event	

user_revealed_secrets_history

A user revealed the secrets history for an account

sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
destinationUserName	Always
The account on the target device to which the event relates	
numberRevealed (<i>as deviceCustomNumber1</i>)	Always
The number of historical secrets that were revealed	
authenticationServiceName (<i>as deviceCustomString6</i>)	When Available
The authentication service to which the account belongs	
destinationHostName	When Available
The host name of the device relating to the event	
destinationName (<i>as deviceCustomString1</i>)	When Available
The name of the device relating to the event	
destinationAddress	When Available
The address of the device relating to the event	

user_rolled_back_device_passwords

A user rolled back the passwords on a device

destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationAddress	Always
The address of the device relating to the event	

user_started_deleting_auth_service

A user triggered the deletion and cleanup of an authentication service

sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
authenticationServiceName (<i>as deviceCustomString6</i>)	Always
The name of the authentication service being deleted	

user_started_deleting_user

A user initiated the deletion of another user on the PxM Platform

destinationUserName Always

The name of the user being deleted

sourceUserName Always

The username of the platform user who initiated the action

droppedActiveConnections (as deviceCustomString6) Always

Whether the PxM Platform dropped active connections from the user in order to initiate the deletion

sourceUserDisplayName (as deviceCustomString2) Always

The human-readable name of the platform user who initiated the action

user_unlocked_device_account

A user unlocked an account on a device

sourceUserName Always

The username of the platform user who initiated the action

sourceUserDisplayName (as deviceCustomString2) Always

The human-readable name of the platform user who initiated the action

destinationUserName Always

The account on the target device to which the event relates

user_unprovisioned_device

A user unprovisioned a device

destinationHostName Always

The host name of the device relating to the event

sourceUserName Always

The username of the platform user who initiated the action

forced (as deviceCustomString6) Always

Whether the device was forcibly unprovisioned

sourceUserDisplayName (as deviceCustomString2) Always

The human-readable name of the platform user who initiated the action

destinationName (as deviceCustomString1) Always

The name of the device relating to the event

destinationAddress Always

The address of the device relating to the event

user_updated_account_mapping_pattern

A user updated an account mapping pattern	
pattern (<i>as deviceCustomString6</i>)	Always
The account mapping pattern that was updated	
sourceUserName	Always
The username of the platform user who initiated the action	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_updated_device_file

A user performed an action that changed a file on a device	
destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
filePath	Always
The full path on the device of the file that was updated	
destinationUserName	Always
The account on the target device to which the event relates	
destinationAddress	Always
The address of the device relating to the event	
deviceAction	Always
The action (append, overwrite, delete) that was taken by the user	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_updated_device_secret

A user updated device credentials

destinationName (<i>as deviceCustomString1</i>)	Always
The name of the device relating to the event	
destinationHostName	Always
The host name of the device relating to the event	
sourceUserName	Always
The username of the platform user who initiated the action	
destinationUserName	Always
The account on the target device to which the event relates	
destinationAddress	Always
The address of the device relating to the event	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	

user_updated_profile_memberships

A user updated the memberships of a profile

profileName (<i>as deviceCustomString6</i>)	Always
The name of the profile for which the users were changed	
sourceUserDisplayName (<i>as deviceCustomString2</i>)	Always
The human-readable name of the platform user who initiated the action	
sourceUserName	Always
The username of the platform user who initiated the action	
entityType (<i>as deviceCustomString5</i>)	Always
The type of entity (user, user_group, device, tool, task) added to or removed from the profile	
removedEntityNames (<i>as deviceCustomString3</i>)	When Available
The named of the entities of the sepcified type removed from the profile	
addedEntityNames (<i>as deviceCustomString4</i>)	When Available
The names of the entities of the specified type added to the profile	

[user_updated_user_group](#)

A user updated a user group

sourceUserName	Always
The username of the platform user who initiated the action	
userGroupName (<i>as deviceCustomString6</i>)	Always
The name of the updated user group	
oldUserGroupName (<i>as deviceCustomString5</i>)	When Available
The previous name of the user group if it has been changed	
removedUserNames (<i>as deviceCustomString2</i>)	When Available
The names of the users who were removed from the group	
addedUserNames (<i>as deviceCustomString3</i>)	When Available
The names of the users who were added to the group	